

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number
WO 2005/042630 A2

(51) International Patent Classification⁷:

C08K 3/00

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/EP2004/052765

(22) International Filing Date:

3 November 2004 (03.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

03256951.9 4 November 2003 (04.11.2003) EP

(71) Applicant (*for all designated States except US*): **HUNTSMAN ADVANCED MATERIALS (SWITZERLAND) GmbH** [CH/CH]; Klybeckstrasse 200, CH-4057 Basel (CH).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): **MILLER, Michelle** [GB/GB]; 18, Brentgovel Street Bury St Edmunds, Suffolk IP33 1EB (GB).

(74) Agents: **BARUH, Colette et al.**; **HUNTSMAN (EUROPE) BVBA**, Intellectual Property Department, Ever-slaan 45, B-3078 Everberg (BE).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



A2

WO 2005/042630

(54) Title: TWO COMPONENT CURABLE COMPOSITIONS

(57) Abstract: A two component reactive composition is described. Each component, before they are mixed together, contains a filler having thin platelet structure, e.g. a nanoclay, and a further filler that interacts with the platelets. The individual components can have a filler loading that makes them flowable and therefore the components can readily be mixed together for ready dispensing. When the components are mixed thoroughly together, the resulting resin may have a viscosity higher than that of the individual components. The loading of the filler is preferably chosen so that the resulting blended resin is capable of being applied on to a vertical surface without experiencing significant slump. The viscosity of the mixed material can be up to 5 to 10 times or more than that of the individual components before mixing. The composition can be used in. adhesives, modelling pastes, coatings, sealants, putties, mastics, stopping compounds, caulking materials, encapsulants and surface coatings, e.g. paints.